

Claims

1. A heat exchanger, especially for motor vehicles,
having flat tubes (2) through which first fluids
5 (FL1a, FL1b) can flow and which can be externally
exposed to a second fluid (FL2) and which are
arranged fundamentally parallel to one another and
transversely to the direction of flow (S2) of the
second fluid (FL2) in at least two rows, each first
10 fluid being assigned at least one row of tubes, with
the flat tubes in a row of tubes being spaced apart
forming flow paths for the second fluid (FL2)
passing through the heat exchanger, cooling fins
being arranged in the flow paths, which in each case
15 extend between adjacent flat tubes (2),
characterized in that multiple corrugated fins (3),
which are arranged in series in the direction of
flow (S2) of the second fluid (FL2) and laterally
offset in relation to one another, are provided as
20 cooling fins and in that multiple corrugated fins
(3) arranged in series are formed from a common
strip (8).
2. The heat exchanger as claimed in claim 1,
25 characterized in that the surfaces (5) of the
corrugated fins (3) are arranged fundamentally
parallel to the direction of flow (S2) of the second
fluid (FL2).
- 30 3. The heat exchanger as claimed in claim 1 or 2,
characterized in that multiple offset corrugated
fins (3) are similarly shaped.
4. The heat exchanger as claimed in any one of claims 1
35 to 3, characterized in that at least one of the
corrugated fins (3) has gills (7) for directing the
second fluid (FL2).

5. The heat exchanger as claimed in claim 4, characterized in that all gills (7) of a fin section (4b) bounded by two flat tubes (2) are angled in the same direction relative to the direction of flow (S2) of the second fluid (FL2).
6. The heat exchanger as claimed in claim 5, characterized in that the gills (7) of two successively offset fin sections (4b) are angled in the same direction.
7. The heat exchanger as claimed in claim 5, characterized in that the gills (7) of two successively offset fin sections (4b) are angled in opposite directions.
8. The heat exchanger as claimed in any one of claims 1 to 7, characterized in that two successively offset fin sections (4b) are fundamentally parallel to one another.
9. The heat exchanger as claimed in claim 8, characterized in that the fin sections (4b) are arranged fundamentally perpendicular to the flat tubes (2).
10. The heat exchanger as claimed in any one of claims 1 to 9, characterized in that the corrugated fins (3) extend for an equal or similar distance in the main direction of flow of the second fluid.
11. The heat exchanger as claimed in any one of claims 1 to 10, characterized in that different rows of tubes have different fluids flowing through them.
12. The heat exchanger as claimed in any one of claims 1 to 10, characterized in that one fluid flows through different rows of tubes.